Saved: 09 APR 2001 12:32:24



Acquisition	Sampling mode real time Memory depth automatic Memory depth 1004pts Sampling rate automatic Sampling rate 10.0 MSa/s Averaging off 9-bit BW Filter off Interpolation off
Channel 1	Scale 2.00 V/div Offset -2.860 V BW limit off Coupling DC Impedance 1M Ohm Attenuation 10.00 : 1 Atten units ratio Skew 0.0 s
Channel 2	Scale 2.00 V/div Offset 1.490 V BW limit off Coupling DC Impedance 1M Ohm Attenuation 10.00 : 1 Atten units ratio Skew 0.0 s
Channel 3	Scale 2.00 V/div Offset 6.390 V BW limit off Coupling DC Impedance 1M Ohm Attenuation 10.00 : 1 Atten units ratio Skew 0.0 s
Channel 4	Scale 2.00 V/div Offset 10 mV BW limit off Coupling DC Impedance 1M Ohm Attenuation 10.00 : 1 Atten units ratio Skew 0.0 s
Time base	Scale 10.0 µs/div Position -2.650000 µs Reference center
Trigger	Mode advanced Sweep triggered Advanced state L X Clock falling X Clock 3 Pattern and Hysteresis normal Holdoff time 60 ns Channel 1 Trigger level 1.25 V Channel 3 Trigger level 1.25 V